

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : CW34 - LOW/HIGH PRESSURE PRESOAK
 Product code : CW34

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Sky Blue Chemical
 760 W. Exchange Road
 Ogden, Utah 84401 - USA
 T (800) 998-2808
www.skybluechemical.com

1.4. Emergency telephone number

Emergency number : Chemtrec 1-800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin Irrit. 2 Causes skin irritation
 Eye Dam. 1 Causes serious eye damage

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
 Hazard statements (GHS US) : Causes skin irritation
 Causes serious eye damage
 Precautionary statements (GHS US) : Wash hands, forearms and face thoroughly after handling.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin: Wash with plenty of water.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Immediately call a poison center or doctor.
 Specific treatment (see supplemental first aid instruction on this label).
 If skin irritation occurs: Get medical advice/attention.
 Take off contaminated clothing and wash it before reuse.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Tetrasodium ethylenediaminetetraacetate	(CAS-No.) 64-02-8	1 – 3	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Eye Dam. 1, H318

CW34 - LOW/HIGH PRESSURE PRESOAK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
butyl glycoether	(CAS-No.) 111-76-2	1 – 3	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2B, H320
UNDECETH-5	(CAS-No.) 34398-01-1	1 – 3	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Disodium metasilicate	(CAS-No.) 6834-92-0	1 – 3	Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
- First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after skin contact : Irritation.
- Symptoms/effects after eye contact : Serious damage to eyes.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

- Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

CW34 - LOW/HIGH PRESSURE PRESOAK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

CW34 - LOW/HIGH PRESSURE PRESOAK	
No additional information available	
Disodium metasilicate (6834-92-0)	
No additional information available	
butyl glycoether (111-76-2)	
USA - ACGIH - Occupational Exposure Limits	
Local name	2-Butoxyethanol (EGBE)
ACGIH TWA (ppm)	20 ppm
Remark (ACGIH)	Eye & URT irr
USA - OSHA - Occupational Exposure Limits	
Local name	2-Butoxyethanol
OSHA PEL (TWA) (mg/m ³)	240 mg/m ³
OSHA PEL (TWA) (ppm)	50 ppm
UNDECETH-5 (34398-01-1)	
No additional information available	
Tetrasodium ethylenediaminetetraacetate (64-02-8)	
No additional information available	

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



CW34 - LOW/HIGH PRESSURE PRESOAK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
pH	: > 11
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 212 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Density	: 8.43 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Disodium metasilicate (6834-92-0)

LD50 oral rat	1153 mg/kg
---------------	------------

CW34 - LOW/HIGH PRESSURE PRESOAK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Disodium metasilicate (6834-92-0)	
LD50 dermal rat	> 5000 mg/kg body weight (EPA OPPTS 870.1200: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 2.06 mg/l (EPA OPPTS 870.1300: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

butyl glycolether (111-76-2)	
LD50 oral rat	1746 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	435 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity; 435 mg/kg bodyweight; Rabbit; Weight of evidence; Equivalent or similar to OECD 402)
LC50 Inhalation - Rat	> 4.26 mg/l (4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

UNDECETH-5 (34398-01-1)	
LD50 oral rat	> 1400 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

Tetrasodium ethylenediaminetetraacetate (64-02-8)	
LD50 oral rat	1780 – 2000 mg/kg (Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	> 5000 mg/kg
LC50 Inhalation - Rat	4.14 mg/l/4h Dust

Skin corrosion/irritation	: Causes skin irritation. pH: > 11
Serious eye damage/irritation	: Causes serious eye damage. pH: > 11
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

butyl glycolether (111-76-2)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

Disodium metasilicate (6834-92-0)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Not classified

Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Serious damage to eyes.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Disodium metasilicate (6834-92-0)	
LC50 fish 1	210 mg/l (ISO 7346-1, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value)
EC50 Daphnia 1	1700 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)

butyl glycolether (111-76-2)	
LC50 fish 1	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Lethal)

CW34 - LOW/HIGH PRESSURE PRESOAK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

butyl glycolether (111-76-2)	
EC50 Daphnia 1	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 (algae)	911 mg/l (72 Hr.)
UNDECETH-5 (34398-01-1)	
LC50 fish 1	1 – 10 mg/l (96 hr.)
EC50 Daphnia 1	1 – 10 mg/l (48 hr.)
EC50 other aquatic organisms 1	1 – 10 mg/l (96 hr.)(Algae)
Tetrasodium ethylenediaminetetraacetate (64-02-8)	
LC50 fish 1	121 mg/l (US EPA, 96 h, Lepomis macrochirus, Static system, Fresh water, Experimental value, Soft water)
EC50 Daphnia 1	625 mg/l (DIN 38412-11, 24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 (algae)	> 100 mg/l (EU Method C.3, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Weight of evidence, Nominal concentration)

12.2. Persistence and degradability

Disodium metasilicate (6834-92-0)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

butyl glycolether (111-76-2)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.71 g O ₂ /g substance
Chemical oxygen demand (COD)	2.2 g O ₂ /g substance
ThOD	2.305 g O ₂ /g substance
BOD (% of ThOD)	0.31

Tetrasodium ethylenediaminetetraacetate (64-02-8)	
Persistence and degradability	Not readily biodegradable in water.
Biochemical oxygen demand (BOD)	< 0.002 g O ₂ /g substance
Chemical oxygen demand (COD)	0.54 – 0.58 g O ₂ /g substance

12.3. Bioaccumulative potential

Disodium metasilicate (6834-92-0)	
Bioaccumulative potential	Not bioaccumulative.

butyl glycolether (111-76-2)	
Partition coefficient n-octanol/water (Log Pow)	0.81 (Experimental value; BASF test; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Tetrasodium ethylenediaminetetraacetate (64-02-8)	
BCF fish 1	1.1 – 1.8 (28 day(s), Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	-13.17 (Estimated value, KOWWIN)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

Disodium metasilicate (6834-92-0)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for adsorption in soil.

butyl glycolether (111-76-2)	
Surface tension	0.027 N/m (25 °C)
Partition coefficient n-octanol/water (Log Koc)	0.451 – 0.882 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

CW34 - LOW/HIGH PRESSURE PRESOAK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Tetrasodium ethylenediaminetetraacetate (64-02-8)	
Partition coefficient n-octanol/water (Log Koc)	2.495 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Low potential for adsorption in soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN3266 Corrosive liquid, basic, inorganic, n.o.s. (Sodium Hydroxide), 8, III
UN-No.(DOT) : UN3266
Proper Shipping Name (DOT) : Corrosive liquid, basic, inorganic, n.o.s.
Sodium Hydroxide
Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136
Packing group (DOT) : III - Minor Danger
Hazard labels (DOT) : 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 241
DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx) : 154
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other : 40 - Stow "clear of living quarters", 52 - Stow "separated from" acids
Emergency Response Guide (ERG) Number : 154
Other information : No supplementary information available.

Transportation of Dangerous Goods

Not applicable

CW34 - LOW/HIGH PRESSURE PRESOAK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea

Transport document description (IMDG)	: UN 3266 CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium Hydroxide), 8, III
UN-No. (IMDG)	: 3266
Proper Shipping Name (IMDG)	: CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S.
Class (IMDG)	: 8 - Corrosive substances
Packing group (IMDG)	: III - substances presenting low danger
Limited quantities (IMDG)	: 5 L

Air transport

Transport document description (IATA)	: UN 3266 Corrosive liquid, basic, inorganic, n.o.s. (Sodium Hydroxide), 8, III
UN-No. (IATA)	: 3266
Proper Shipping Name (IATA)	: Corrosive liquid, basic, inorganic, n.o.s.
Class (IATA)	: 8 - Corrosives
Packing group (IATA)	: III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed as Active, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

di(tetramethylammonium)(29H,31H-phthalocyanin-N29,N30,N31,N32)disulfonamide disulfonate, cuprate(2-)complex, derivatives	CAS-No. 12222-04-7	0.1 – 1%
Polysorbate 20	CAS-No.	0.1 – 1%
BLUE AGAVE	CAS-No.	0.1 – 1%

Contains chemical(s) subject to TSCA 12b export notification if product is shipped outside the U.S

Acetaldehyde	CAS-No. 75-07-0	< 0.1%
--------------	-----------------	--------

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

ethylene glycol	CAS-No. 107-21-1	< 0.1%
Ethylene oxide	CAS-No. 75-21-8	< 0.1%
Acetaldehyde	CAS-No. 75-07-0	< 0.1%

butyl glycoether (111-76-2)

SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
-------------------------------------	---

ethylene glycol (107-21-1)

Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	5000 lb

UNDECETH-5 (34398-01-1)

EPA TSCA Regulatory Flag	N - N - indicates a polymeric substance containing no free-radical initiator in its Inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used. P - P - indicates a commenced Premanufacture Notice (PMN) substance. XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

Ethylene oxide (75-21-8)

Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	10 lb
RQ (Reportable quantity, section 304 of EPA's List of Lists)	10 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	1000 lb

CW34 - LOW/HIGH PRESSURE PRESOAK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetaldehyde (75-07-0)	
Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	1000 lb
Tetrasodium ethylenediaminetetraacetate (64-02-8)	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
Sodium hydroxide (1310-73-2)	
CERCLA RQ	1000 lb

15.2. International regulations

Ethylene oxide (75-21-8)	
Listed on IARC (International Agency for Research on Cancer)	
Listed as carcinogen on NTP (National Toxicology Program)	
Acetaldehyde (75-07-0)	
Listed as carcinogen on NTP (National Toxicology Program)	

15.3. US State regulations

⚠ WARNING: This product can expose you to Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
butyl glycoether(111-76-2)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
ethylene glycol(107-21-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Ethylene oxide(75-21-8)	U.S. - New Jersey - Right to Know Hazardous Substance List
Acetaldehyde(75-07-0)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Sodium hydroxide(1310-73-2)	U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 02/18/2022

Full text of H-phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Eye Irrit. 2B	Serious eye damage/eye irritation Category 2B
Flam. Liq. 4	Flammable liquids Category 4
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation

CW34 - LOW/HIGH PRESSURE PRESOAK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SDS US (GHS HazCom 2012)

The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.